

Spectral Gamma-Ray Borehole Log Data Report

Page 1 of 2

Borehole

52-02-09

Log Event A

Borehole Information

Farm : \underline{TY} Tank : $\underline{TY-102}$ Site Number : $\underline{299-W10-93}$

N-Coord : 42,600 **W-Coord** : 76,002 **TOC** Elevation : 669.32

Water Level, ft : Date Drilled : 12/31/1971

Casing Record

Type: Steel-welded Thickness: 0.280 ID, in.: 6

Top Depth, ft. : $\underline{0}$ Bottom Depth, ft. : $\underline{100}$

Borehole Notes:

According to the driller's records, this borehole was not perforated or grouted. The casing thickness is presumed to be 0.280 in., on the basis of published thickness for schedule-40, 6-in. steel tubing. The top of the casing, which is the zero reference for the SGLS, is approximately 0.6 ft below the tank farm grade inside a plastic well box.

Equipment Information

 Logging System :
 2
 Detector Type :
 HPGe
 Detector Efficiency:
 35.0 %

 Calibration Date :
 10/1995
 Calibration Reference :
 GJPO-HAN-3
 Logging Procedure : P-GJPO-1783

Log Run Information

Log Run Number : 1 Log Run Date : 5/10/1996 Logging Engineer: Alan Pearson

Start Depth, ft.: $\underline{98.5}$ Counting Time, sec.: $\underline{100}$ L/R: \underline{L} Shield: \underline{N} Finish Depth, ft.: $\underline{20.0}$ MSA Interval, ft.: $\underline{0.5}$ Log Speed, ft/min.: $\underline{n/a}$

Log Run Number: 2 Log Run Date: 5/13/1996 Logging Engineer: Kim Benham

Start Depth, ft.: $\underline{21.0}$ Counting Time, sec.: $\underline{100}$ L/R: \underline{L} Shield: \underline{N} Finish Depth, ft.: $\underline{0.0}$ MSA Interval, ft.: $\underline{0.5}$ Log Speed, ft/min.: \underline{n}/a



Spectral Gamma-Ray Borehole Log Data Report

Page 2 of 2

Borehole 52-02-09

Log Event A

Analysis Information

Analyst: S.D. Barry

Data Processing Reference : P-GJPO-1787 Analysis Date : 1/27/1997

Analysis Notes:

This borehole was logged in two log runs. The pre- and post-survey field verification spectra met the acceptance criteria established for the peak shape and detector efficiency, confirming that the SGLS was operating within specifications. The energy calibration and peak-shape calibration from these spectra were used to establish the channel-to-energy parameters used in processing the spectra acquired during the logging operation.

Casing correction factors for a 0.280-in.-thick steel casing were applied during analysis.

The only man-made radionuclide detected in this borehole was Cs-137. The presence of Cs-137 was only detected at the ground surface with a maximum concentration of 0.36 pCi/g.

The change in U-238 concentration values at about 20 ft is associated with the change in log runs. This change is probably due to radon venting up the borehole. The 609-keV spectral peak that is used to calculate the U-238 concentration is only accurate if the Bi-214 and U-238 are in secular equilibrium. Because radon gas is an intermediate member of the U-238 decay chain, the equilibrium condition will be disturbed along with changes in the weather conditions in the vicinity of the borehole. The concentration of the Rn-222 in the borehole does not necessarily remain constant between log runs.

The K-40 concentration values begin to increase at about 52 ft and the Th-232 and U-238 concentrations begin to increase at about 92 ft.

Additional information and interpretations of log data are included in the main body of the Tank Summary Data Report for tank TY-102.

Log Plot Notes:

Separate log plots show the man-made (Cs-137) and the naturally occurring radionuclides (KUT). The natural radionuclides can be used for lithology interpretations. The headings of the plots identify the specific gamma rays used to calculate the concentrations.

Uncertainty bars on the plots show the statistical uncertainties for the measurements as 95-percent confidence intervals. Open circles on the plots give the MDL. The MDL of a radionuclide represents the lowest concentration at which positive identification of a gamma-ray peak is statistically defensible.

A combination plot includes the man-made and natural radionuclides, the total gamma derived from the spectral data, and the Tank Farms gross gamma log. The gross gamma plot displays the latest available digital data. No attempt has been made to adjust the depths of the gross gamma logs to coincide with the SGLS data.